

Technical data sheet for industrial trucks acc. to VDI 2198				1KG=2.2LB 1INCH=25.4MM		
Distinguishing mark	1.2	Manufacturer`s type designation		HPT-A	HPT-D	HPT-C
	1.3	Drive		Manual	Manual	Manual
	1.4	Operator type		Hand	Hand	Hand
	1.5	Load Capacity / rated load	Q(t)	2.0/2.5/3.0	2.0/2.5/3.0	2.0/2.5/3.0
	1.6	Load centre distance	c(mm)	600	600	600
	1.8	Load distance ,centre of drive axle to fork	x(mm)	972	972	972
	1.9	Wheelbase	Y(mm)	1218	1218	1218
Weight	2.1	Service weight(with Pu double wheels)	kg	70/72/77	66/68/72	68/70/75
	2.2	Axle loading, laden front/rear	kg	1776/819	1740/853	1810/784
	2.3	Axle loading, unladen front/rear	kg	22/49	23/45	23/47
Tyres, chassis	3.1	Tyres				
	3.2	Tyre size, front	mm	Æ80×70	Æ80×70	Æ80×70
	3.3	Tyre size, rear	mm	Æ 200×50	Æ 200×50	Æ 200×50
	3.4	Additional wheels(dimensions)	mm	—	—	—
	3.5	Wheels, number front/rear(x=driven wheels)		2/2 or 2/4	2/2 or 2/4	2/2 or 2/4
	3.6	Tread, front	b10 (mm)	540	540	540
	3.7	Tread, rear	b11 (mm)	380	380	270
Dimensions	4.4	Lift height	h3 (mm)	115	115	115
	4.9	Height of tiller	h14(mm)	1230	1230	1230
	4.15	Height, lowered	h13 (mm)	85	85	85
	4.19	Overall length	l1 (mm)	1545	1521	1540
	4.2	Length to face of forks	l2 (mm)	395	371	390
	4.21	Overall width	b1 (mm)	540	540	540
	4.22	Fork dimensions	s/e/l (mm)	48/160/1150 ¹⁾	48/160/1150 ¹⁾	48/160/1150 ¹⁾
	4.25	Distance between fork- arms	b5 (mm)	540	540	540
	4.32	Ground clearance, centre of wheelbase	m2 (mm)	37	37	37
	4.34	Aisle width for pallets 800X1200 lengthways	Ast (mm)	2088	2064	2084
	4.35	Turning radius	Wa (mm)	1275	1251	1271